

## PUF-0406-03B

### Oilite® Polymer Poly-Safe Ultra-FDA

#### Flange

High-Performance Food Contact, Max  
PV 15,000



#### Dimensions & Tolerances

Nominal ID: 0.25 "  
ID Max: 0.2535 "  
ID Min: 0.2525 "  
Nominal OD: 0.375 "  
OD Max: 0.3768 "  
OD Min: 0.3758 "  
Length: 0.375 " ±0.005  
Flange OD: 0.5 " ±0.005  
Flange Thickness: 0.0625 " ±0.0025  
Weight: lbs / 0 g

#### Press Fit

Housing Bore: 0.3743 " ±0.0005  
Shaft Diameter: 0.24857 " ±0.0002

#### Temperature

Max Temp F / C: 220 / 104  
Min Temp F / C: -40 / -40

#### Pressure Ratings

Max P: 1500 (psi)  
Max V: 1000 (sf/m)  
Max PV: 15000 (lb-ft/in<sup>2</sup>-min)  
Calculated P: 0 (psi)  
Calculated V: 0 (sf/m)  
Calculated PV: 0 (lb-ft/in<sup>2</sup>-min)

#### Material Specifications

Lubrication: Self-Lubricating  
Dry Running  
Regulations: USDA-H1 Certified  
Food Contact Certified  
Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Washdown  
Chemical Resistant  
Corrosion Resistant  
Electrical Insulation  
STEAM  
Specifications Met: