

## SOAMP2025-25

### Super Oilite® M-Series

### Metric/PLUS

#### Sleeve

PTFE Additive-Reduced Friction  
Synthetic Oilite® Plus-SPD™. Extreme  
Performance-Unique Applications.

Temp Range -50°C to +149°C



#### Dimensions & Tolerances

Nominal ID: 20 mm  
ID Max: 20.035 mm  
ID Min: 20.01 mm  
Nominal OD: 25 mm  
OD Max: 25.065 mm  
OD Min: 25.04 mm  
Length: 25 mm  $\pm 0.25$   
Weight: 0.068 lbs / 30.8 g

#### Press Fit

Housing Bore: 24.98907 mm  $\pm 0.013$   
Shaft Diameter: 19.89955 mm  $\pm 0.005$

#### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -60 / -51

#### Pressure Ratings

Max P: 27.56 (N/mm<sup>2</sup>)  
Max V: 1.14 (m/s)  
Max PV: 1.225 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Specifications Met: SAE 863  
ASTM B-439 GR 4  
FC-2000-K30