

## SOFMP2026-30

### Super Oilite® M-Series

### Metric/PLUS

#### Flange

PTFE Additive-Reduced Friction

Synthetic Oilite® Plus-SPD™. Extreme

Performance-Unique Applications.

Temp Range -50°C to +149°C



#### Dimensions & Tolerances

Nominal ID: 20 mm  
ID Max: 20.035 mm  
ID Min: 20.01 mm  
Nominal OD: 26 mm  
OD Max: 26.07 mm  
OD Min: 26.04 mm  
Length: 30 mm  $\pm 0.25$   
Flange OD: 32 mm  $\pm 0.25$   
Flange Thickness: 3 mm  $\pm 0.125$   
Weight: 0.097 lbs / 44 g

#### Press Fit

Housing Bore: 25.99326 mm  $\pm 0.013$   
Shaft Diameter: 19.89882 mm  $\pm 0.005$

#### Temperature

Max Temp F / C: 300 / 149  
Min Temp F / C: -60 / -51

#### Pressure Ratings

Max P: 27.56 (N/mm<sup>2</sup>)  
Max V: 1.14 (m/s)  
Max PV: 1.225 (N-M/mm<sup>2</sup>-s)  
Calculated P: 0 (N/mm<sup>2</sup>)  
Calculated V: 0 (m/s)  
Calculated PV: 0 (N-M/mm<sup>2</sup>-s)

#### Material Specifications

Lubrication: Self-Lubricating  
Regulations: Lead-Free  
Conflict Free  
RoHS Certified  
Reach Certified  
Engineering Preferences: Conducts Electricity  
Specifications Met: SAE 863  
ASTM B-439 GR 4  
FC-2000-K30